

CARDEV

Oil Filtration and Coolant Handling Specialists



DATA SHEET

1S250P AIR

Removes Contaminants

Extends Oil Life

Reduces Component Wear

Removes all Water

Saves Machine Downtime

Reduces Disposal Costs

Simple to Install & Use

Low Maintenance Costs

Built in Sampling Points



AIR OPERATED

Cardev International Ltd

Ripon Way, Harrogate, HG1 2AU
Tel: 01423 522911 Fax: 01423 530043
Email: sales@cardev.co.uk or visit our
website at: www.cardev.co.uk



Cardev International Ltd

Ripon Way, Harrogate, HG1 2AU Tel: 01423 522911 Fax: 01423 530043
 e-mail: sales@cardev.co.uk web: www.cardev.co.uk



Industrial Filtration



Biodegradable Lubricants

| 1S-250P-AIR - SPECIFICATION | | |
|------------------------------------|---|--------|
| Pump Performance | 250 litres/hour @ 2.0 bar with 5.0 bar inlet air pressure. (ISO 46 Hydraulic oil at 40°C) | |
| Pump Suction Lift | Max Lift Dry 2.5-3 metres | |
| Operating Temperature | 10-82°C | |
| Dimensions | Length | 340 mm |
| | Width | 240 mm |
| | Height | 585 mm |
| Weight | 16 kg | |
| Filtration System | 1 x SDU H8 | |
| Cartridge Type | 1 x SDFC—Fitted as standard. Supplied in boxes of 6 | |
| Accessories | 6 metres of reinforced 3/4" hose with quick release couplings SDFC-P Cartridges for water based fluids | |

Description

The 1S250P AIR Micron Filtration System is a compact free standing off line oil cleaning and filtration system, capable of removing fine dirt particles and totally removing water. Filter cartridges are also available for use on water based fluids



Certificate No: 8445

Registered in England No: 1753106
 VAT No: 386 0916 27

11.01.05.SS 1S250PAIRINFO.PUB