



# DATA SHEET

## 2S500P AIR

***Removes Contaminants***

***Extends Oil Life***

***Reduces Component Wear***

***Removes all Water***

***Saves Machine Downtime***

***Reduces Disposal Costs***

***Simple to Install & Use***

***Low Maintenance Costs***

***Built in Sampling Points***



**AIR OPERATED**

Cardev International Ltd

Ripon Way, Harrogate, HG1 2AU  
Tel: 01423 522911 Fax: 01423 530043  
Email: sales@cardev.co.uk or visit our  
website at: www.cardev.co.uk



# Cardev International Ltd

Ripon Way, Harrogate, HG1 2AU Tel: 01423 522911 Fax: 01423 530043  
 e-mail: sales@cardev.co.uk web: www.cardev.co.uk



Industrial Filtration



Biodegradable Lubricants

<b>2S500P AIR - SPECIFICATION</b>		
Pump Performance	500 litres/hour @ 2.0 bar with 5.0 bar inlet air pressure. (ISO 46 Hydraulic oil at 40°C)	
Pump Suction Lift	Max Lift Dry 2.5-3 metres	
Operating Temperature	10-82°C	
Dimensions	Length	540 mm
	Width	240 mm
	Height	585 mm
Weight	25 kg	
Filtration System	2 x SDU H8	
Cartridge Type	2 x SDFC—Fitted as standard. Supplied in boxes of 6	
Accessories	6 metres of reinforced 3/4" hose with quick release couplings SDFC-P Cartridges for water based fluids	

## Description

The 2S500P AIR Micron Filtration System is a compact free standing off line oil cleaning and filtration system, capable of removing fine dirt particles and totally removing water. Filter cartridges are also available for use on water based fluids



Certificate No: 8445

Registered in England No: 1753106  
 VAT No: 386 0916 27

11.01.05.SS 2S500PAIRINFO.PUB