



# DATA SHEET

## 6S1500E AIR

***Removes Contaminants***

***Extends Oil Life***

***Reduces Component Wear***

***Removes all Water***

***Saves Machine Downtime***

***Reduces Disposal Costs***

***Simple to Install & Use***

***Low Maintenance Costs***

***Built in Sampling Points***



**AIR OPERATED**

Cardev International Ltd

Ripon Way, Harrogate, HG1 2AU  
Tel: 01423 522911 Fax: 01423 530043  
Email: sales@cardev.co.uk or visit our  
website at: www.cardev.co.uk



# Cardev International Ltd

Ripon Way, Harrogate, HG1 2AU Tel: 01423 522911 Fax: 01423 530043  
 e-mail: sales@cardev.co.uk web: www.cardev.co.uk



Industrial Filtration



Biodegradable Lubricants

<b>6S1500EAIR - SPECIFICATION</b>		
Pump Performance	1500 litres/hour @ 2.6 bar (ISO 46 Hydraulic oil at 40°C) 1600 litres/hr @ 1 bar—transfer rate using valve	
Pump Suction Lift	Self priming to 5.5 metres	
Pump Motor	0.75 kW equivalent air motor 1500 rpm flange mounted Max. air consumption 45 cfm/1.27m <sup>3</sup> /min	
Operating Temperature	10-90°C	
Dimensions	Length	1180 mm
	Width	595 mm
	Height	1000 mm
	(with handle removed)	780 mm
Weight	119 kg	
Filtration System	6 x SDUFB-C	
Cartridge Type	6 x SDFC—Fitted as standard. Supplied in boxes of 6	
Accessories	6 metres of reinforced 1" hose with quick release couplings	
Options	110V/230V and 3-phase 45 cm bag-type pre-filter Flow meter, Polypropylene Cartridges for water based fluid	

## Description

The 6S1500E AIR Micron Filtration System is a compact free standing off line oil cleaning and filtration system, capable of removing fine dirt particles and totally removing water. Filter cartridges are also available for use on water based fluids.



Certificate No: 8445

Registered in England No: 1753106  
 VAT No: 386 0916 27

11.01.05.SS 6S1500EAIRINFO.PUB